

HOLEX. Light chain pipe wrench

Profiled handle with toothed face and strong steel chain.

Material: Chrome vanadium steel.

Spare part: Spare chain see No. 709910.



Pipe Ø	inch	3/8-4
82A 81 1100	Light chain pipe wrench	XXX
Chain length	mm	410
Handle length	mm	300

HOLEX. Chain pipe wrenches

81 1200 – With double-sided toothed jaws. Strong steel chain and solid lever handle. Body and jaws drop-forged.

Material:

81 1200 – Special tool steel; handle painted.



Type		1/2-2 1/2	1-6
82A 81 1200	Chain pipe wrench	XXX	XXX
82A 81 1220	Spare chain with endpiece	XXX	XXX
Chain length	mm	420	765
Handle length (81 1200)	mm	685	1120
Pipe Ø (81 1200)	inch	1/2 – 2.1/2	1 – 6

HOLEX. Belt wrenches (strap wrenches) with fabric belt

81 1400/1500 – Profiled shank; strong, wear-resistant, non-slip fabric belt, exchangeable.

Application: For gripping round parts, especially those with larger Ø.

81 1400 – Particularly for components with chrome-plated, polished surfaces (fittings).



Band width / Band length	mm	20/600	25/820	27/930
82A 81 1400	Strap wrench	–	–	XXX
82A 81 1410	Spare strap for No. 811400	–	–	XXX
82A 81 1500	Belt wrench	XXX	XXX	–
82A 81 1510	Spare fabric belt for No. 811500	XXX	XXX	–
overall length of the shank (81 1400, 81 1500)	mm	225	280	300
Clamping capacity Ø (81 1400)	inch	–	–	1 - 8
Clamping capacity Ø (81 1400, 81 1500)	mm	160	220	230

HOLEX. Basin wrench

Forged shank with swivelling handle and swing steel claw for clockwise and anticlockwise operation. Wrench painted. Range 24 – 32 mm.

Material: Chrome vanadium steel.



		overall length mm
82A 81 2100	Basin wrench	XXX 235

VBW. Fittings wrench

With rapid ratchet adjustment and clamping lever. Leverage delivers large clamping force. Gear rack and support lever hardened, smooth jaws, head bright.

Material: Chrome-manganese steel.

Application: For screwing fittings.



overall length	mm	260
83E 81 3000	Rapid clamping fittings wrench	XXX
Jaw length	mm	40
Jaw capacity	mm	70

Smooth jaws