



LED cordless lamp 0 version without battery, 18.0 V, Type: M18HOSALC



Order data

Order number	073211 M18HOSALC
GTIN	4058546340490
Item class	03L

Description

Version:

Robust Li-Ion battery lights with high light intensity.

- **The shock-proof floodlight head with 3 separate and individually tiltable LED rows can be rotated by 180° and tilted by 240°.**
- **Integral M18™ and 2.1 Ah USB charger. The floodlight can thus be operated using rechargeable battery or mains power.**
- **The stand with reinforced feet can be pulled out from 1.0 m to 2.2 m, thus permitting lighting from above and working that is free of shadows. The stand has a low centre of gravity for maximum stability.**

Suitable for :

Milwaukee 18 V batteries (No. 073816 MB18 and 073827 MB18).

Supplied with:

Cordless lamp without battery and without charger.

suitable battery - supplier / battery type / voltage: Milwaukee type B 18 V

Manufacturer's designation: M18 HOSALC-0

Pivoting range of the lamp head: 240 degrees

Illumination: 6000 lm

Illumination step 2: 4000 lm

Working life: 3.5 h

Number of rechargeable batteries contained: 0

Technical description

ATEX zone	no
Pivoting range of the lamp head	240 degrees
Power supply	Rechargeable battery-powered
Illumination step 2	4000 lm
Lighting life stage 2	5 h
Weight including rechargeable battery	11100 g
Number of rechargeable batteries contained	0
Working life	3.5 h
Type of rechargeable battery	Lithium-ion
Bulb	LED lamp
Battery voltage	18 V
Illumination	6000 lm
Lighting life stage 3	10 h
Manufacturer's designation	M18 HOSALC-0
Product name attribute	18.0 V
suitable battery - supplier / battery type / voltage	Milwaukee type B 18 V
Type of product	Work lamp