LEDLENSER

LED torch, Type: P7



Order data

Order number	081485 P7
GTIN	4058205009898
Item class	04B

Description

Version:

High-performance line of LED LENSER for general- purpose use. Drop tested from a 1 m height. LED lenses are amongst the technology leaders for LED torches. Within the **splash-proof aluminium housing**, all the contacts are gold-plated, **high-quality lenses** gather the light uniformly and without losses. All these high-class torches incorporate the patented **Advanced Focus System**.

· Advanced Focus System (AFS)

The Advanced Focus System is a combination of lens and reflector, thus incorporating the advantages of both systems. The result is an outstanding concentration of light in focus, together with a largely homogeneous unfocussed light beam. This makes the AFS one of the best focussing systems in the world for LED lamps.

· Rapid Focus

Conventional focussing systems with twist knobs must be operated manually with both hands. Rapid Focus, on the other hand, allows quick adjustment of the light beam with only one hand.

Supplied with:

Including battery No. 081557 LR3. IP Index of Protection: IP X4 Illumination: 450 lm Illumination step 2: 40 lm Working life: 25 h Lighting life stage 2: 25 h Advanced Focus System (AFS): yes Rapid Focus: yes

Technical description

Data sheet

Number of batteries contained4Manufacturer's designationP7Advanced Focus System (AFS)yesBattery typeLR3Head Ø37 mmIllumination450 lmIP Index of ProtectionIP X4Illumination step 240 lmWorking life25 hIncluding belt pocketyesRapid Focus25 hLighting life stage 225 hOverall length130 mm	Weight	175 g
Advanced Focus System (AFS)yesBattery typeLR3Head Ø37 mmIllumination450 lmIP Index of ProtectionIP X4Illumination step 240 lmWorking life25 hIncluding belt pocketyesRapid FocusyesLighting life stage 225 h	Number of batteries contained	4
Battery typeLR3Head Ø37 mmIllumination450 lmIP Index of ProtectionIP X4Illumination step 240 lmWorking life25 hIncluding belt pocketyesRapid FocusyesLighting life stage 225 h	Manufacturer's designation	Р7
Head Ø37 mmIllumination450 lmIP Index of ProtectionIP X4Illumination step 240 lmWorking life25 hIncluding belt pocketyesRapid FocusyesLighting life stage 225 h	Advanced Focus System (AFS)	yes
Illumination450 lmIP Index of ProtectionIP X4Illumination step 240 lmWorking life25 hIncluding belt pocketyesRapid FocusyesLighting life stage 225 h	Battery type	LR3
IP Index of ProtectionIP X4Illumination step 240 lmWorking life25 hIncluding belt pocketyesRapid FocusyesLighting life stage 225 h	Head Ø	37 mm
Illumination step 240 lmWorking life25 hIncluding belt pocketyesRapid FocusyesLighting life stage 225 h	Illumination	450 lm
Working life25 hIncluding belt pocketyesRapid FocusyesLighting life stage 225 h	IP Index of Protection	IP X4
Including belt pocketyesRapid FocusyesLighting life stage 225 h	Illumination step 2	40 lm
Rapid FocusyesLighting life stage 225 h	Working life	25 h
Lighting life stage 2 25 h	Including belt pocket	yes
	Rapid Focus	yes
Overall length 130 mm	Lighting life stage 2	25 h
	Overall length	130 mm
Power supply Battery-powered	Power supply	Battery-powered
Type of product Flashlight	Type of product	Flashlight

Accessories

Alkaline-manganese batteries International size LR3

081556 LR3