



Battery charger, Type: 4ULTRA



Order data

Order number	081590 4ULTRA
GTIN	4013674144679
Item class	08C

Description

Version:

Microprocessor-controlled charging and servicing stations for battery cells with **individual channel monitoring** and battery fault detection. Status display for each charging slot, automatic charging switch-off, overload protection and **trickle charging**. Input voltage 100–240 V. With LC display for detailed monitoring of the charging process. Additional USB-A charging output 5 V, 1000 mA, mains plug (100 - 240 V).

Application:

NiMH/NiCd battery charging points: 1-4 × Micro AAA / Mignon AA or 1-3 × Baby C or 1-2 × Mono D.

Li-Ion battery charging points: 1-4 × 18650, 18500, 17670, 16340, 14500 etc. or 1-3 × 26650, 26500, 25500, 22650 or 1-2 × 3265.

Attention:

German version. Order free UK adapter plug No. 08 1172_GB

Interface: Digimatic interface

maximum charging current: 2 A

Maximum number of charging points: 4

Number of charging slots for USB: 1

Length: 170 mm

Width: 110 mm

Height: 37.5 mm

Technical description

maximum charging current	2 A
Length	170 mm
Height	37.5 mm
Width	110 mm
Maximum number of charging points	4
Number of charging slots for USB	1
Nominal voltage	100 - 240 V
Interface	Digimatic interface
Type of product	Battery charger