



Attachment eye Quick Lift DSR, Thread \varnothing : M20X2,5



Order data

Order number	086454 M20X2,5
GTIN	2050002053878
Item class	08Y

Description

Version:

Compact, high-strength steel Quick Lift DSR attachment eye for screwing in. Rotates 360°, pivots 180°. Time saving of up to 80% compared with screwing in a traditional attachment eye (DSR vs. Quick Lift DSR). **Can be rotated under load.** Easy to use as the system is purely mechanical. Maintenance-free, safe and reliable. The Quick Lift DSR can be fastened in the internal thread in seconds by pressing in the screw head. This is a purely mechanical process based on actuating a spring.

Note:

SF 5:1 = Safety Factor 5.

Lifting capacity WLL SF 5:1: 1.7 t

Thread length L: 30 mm

Internal hexagon size across flats S: 40 mm

Height of screw head A: 55 mm

Height of centre divider B: 55 mm

Screw head \varnothing C: 60 mm

Technical description

Height of screw head A	55 mm
------------------------	-------

Thread length L	30 mm
Eye width E	55 mm
Thread Ø	M20×2.5
Height of centre divider B	55 mm
Screw head Ø C	60 mm
Internal hexagon size across flats S	40 mm
Distance from centre divider to eye D	83 mm
Eye thickness F	25 mm
Weight	2.6 kg
Attachment eye width G	115 mm
Lifting capacity WLL SF 5:1	1.7 t
Type of product	Attachment eye