



Attachment eye Quick Lift DSR, Thread Ø: M8X1,25



Order data

Order number	086454 M8X1,25
GTIN	2050002053823
Item class	08Y

Description

Version:

Compact, high-strength steel Quick Lift DSR attachment eye for screwing in. Rotates 360°, pivots 180°. Time saving of up to 80% compared with screwing in a traditional attachment eye (DSR vs. Quick Lift DSR). **Can be rotated under load.** Easy to use as the system is purely mechanical. Maintenance-free, safe and reliable. The Quick Lift DSR can be fastened in the internal thread in seconds by pressing in the screw head. This is a purely mechanical process based on actuating a spring.

Note:

SF 5:1 = Safety Factor 5.

Lifting capacity WLL SF 5:1: 0.25 t

Thread length L: 17.5 mm

Internal hexagon size across flats S: 18 mm

Height of screw head A: 31 mm

Height of centre divider B: 30 mm

Screw head Ø C: 30 mm

Technical description

Internal hexagon size across flats S	18 mm
--------------------------------------	-------

Thread length L	17.5 mm
Eye thickness F	14 mm
Height of screw head A	31 mm
Height of centre divider B	30 mm
Eye width E	27 mm
Lifting capacity WLL SF 5:1	0.25 t
Weight	0.3 kg
Attachment eye width G	53 mm
Distance from centre divider to eye D	38 mm
Thread Ø	M8x1.25
Screw head Ø C	30 mm
Type of product	Attachment eye