


HOLEX CleverDrill HSS jobber drill, uncoated, Ø DC h8: 6,1 mm

Order data

Order number	113005 6,1
GTIN	4045197952301
Item class	12B

Description
Version:

Sturdy drills for all standard applications. Improved spot drilling behaviour due to cross-ground form. Standard core thickness and core taper. Profile ground. Surface: Bronze-coloured tempered helical flutes.

Through-coolant: no

Standard: DIN 1897

Tolerance nominal Ø: h8

Point angle: 130 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth L_2 : 21.85 mm

Flute length L_c : 31 mm

Overall length L: 70 mm

Shank Ø D_s : 6.1 mm

Feed f in steel < 750 N/mm²: 0.08 mm/rev.

Technical description

Number of cutting edges Z	2
Shank Ø D_s	6.1 mm
Standard	DIN 1897
Overall length L	70 mm
Flute length L_c	31 mm
Nominal Ø D_c	6.1 mm
Tolerance nominal Ø	h8

recommended maximum drilling depth L_2	21.85 mm
Feed f in steel $< 750 \text{ N/mm}^2$	0.08 mm/rev.
Point angle	130 degrees
Series	HOLEX CleverDrill
Coating	uncoated
Tool material	HSS
Type	N
Shank	Plain shank
Through-coolant	no
Colour ring	without
Type of product	Jobber drill