

Garant
Stub drill HSS-E, TiAlN, Ø DC h8: 1,2 mm

Order data

Order number	113265 1,2
GTIN	4062406233860
Item class	11B

Description
Version:

High concentricity and **special chip flutes** ensure precise bores.

With point geometry shape C from size 2.4 mm.

Advantage:

Ideal for drilling shallow holes (approx. 2 - 4×D) on NC machines and automatic machines.

Recommendation:
Maximum drilling depth:

flute length (see table) less 1.5×nominal Ø.

Through-coolant: no

Standard: DIN 1897

Tolerance nominal Ø: h8

Point angle: 118 degrees

Number of cutting edges Z: 2

Flute length L_c : 8 mm

Overall length L: 30 mm

Shank Ø D_s : 1.2 mm

Feed f in stainless steel < 900 N/mm²: 0.02 mm/rev.

Technical description

Point angle	118 degrees
Tolerance nominal Ø	h8
Nominal Ø D_c	1.2 mm
Number of cutting edges Z	2
Standard	DIN 1897

Shank $\varnothing D_s$	1.2 mm
Flute length L_c	8 mm
Feed f in stainless steel $< 900 \text{ N/mm}^2$	0.02 mm/rev.
Overall length L	30 mm
Coating	TiAlN
Tool material	HSS E
Shank	Plain shank
Through-coolant	no
Colour ring	green
Type of product	Jobber drill