

Garant
Stub drill HSS-E, TiAlN, Ø DC h8: 1,5 mm

Order data

Order number	113265 1,5
GTIN	4062406233921
Item class	11B

Description
Version:

High concentricity and **special chip flutes** ensure precise bores.

With point geometry shape C from size 2.4 mm.

Advantage:

Ideal for drilling shallow holes (approx. 2 - 4×D) on NC machines and automatic machines.

Recommendation:
Maximum drilling depth:

flute length (see table) less 1.5×nominal Ø.

Through-coolant: no

Standard: DIN 1897

Tolerance nominal Ø: h8

Point angle: 118 degrees

Number of cutting edges Z: 2

Flute length L_c : 9 mm

Overall length L: 32 mm

Shank Ø D_s : 1.5 mm

Feed f in stainless steel < 900 N/mm²: 0.02 mm/rev.

Technical description

Tolerance nominal Ø	h8
Flute length L_c	9 mm
Number of cutting edges Z	2
Point angle	118 degrees
Shank Ø D_s	1.5 mm

Nominal $\varnothing D_c$	1.5 mm
Feed f in stainless steel < 900 N/mm ²	0.02 mm/rev.
Overall length L	32 mm
Standard	DIN 1897
Coating	TiAlN
Tool material	HSS E
Shank	Plain shank
Through-coolant	no
Colour ring	green
Type of product	Jobber drill

Accessories

Stub drill set HSS-E No. 113265, refill set without a case Type 1-10	113790 1-10
Stub drill set HSS-E No. 113265, with case Type 1-10	113780 1-10