

Garant
Stub drill HSS-E, TiAlN, Ø DC h8: 4,4 mm

Order data

Order number	113265 4,4
GTIN	4062406234508
Item class	11B

Description
Version:

High concentricity and **special chip flutes** ensure precise bores.

With point geometry shape C from size 2.4 mm.

Advantage:

Ideal for drilling shallow holes (approx. 2 - 4×D) on NC machines and automatic machines.

Recommendation:
Maximum drilling depth:

$$L_2 = L_c - 1.5 \times D_c$$

Through-coolant: no

Standard: DIN 1897

Tolerance nominal Ø: h8

Point angle: 118 degrees

Number of cutting edges Z: 2

Flute length L_c : 24 mm

Overall length L: 58 mm

Shank Ø D_s : 4.4 mm

Feed f in stainless steel < 900 N/mm²: 0.03 mm/rev.

Technical description

Shank Ø D_s	4.4 mm
Overall length L	58 mm
Point angle	118 degrees
Flute length L_c	24 mm
Nominal Ø D_c	4.4 mm

Standard	DIN 1897
Tolerance nominal Ø	h8
Feed f in stainless steel < 900 N/mm ²	0.03 mm/rev.
Number of cutting edges Z	2
Coating	TiAlN
Tool material	HSS E
Shank	Plain shank
Through-coolant	no
Colour ring	green
Type of product	Jobber drill