

**Garant**
**Stub drill HSS-E, TiAlN, Ø DC h8: 6,3 mm**

**Order data**

Order number	113265 6,3
GTIN	4062406234881
Item class	11B

**Description**
**Version:**

**High concentricity** and **special chip flutes** ensure precise bores.

With point geometry shape C from size 2.4 mm.

**Advantage:**

**Ideal for drilling shallow holes (approx. 2 - 4×D)** on NC machines and automatic machines.

**Recommendation:**
**Maximum drilling depth:**

$$L_2 = L_c - 1.5 \times D_c$$

Through-coolant: no

Standard: DIN 1897

Tolerance nominal Ø: h8

Point angle: 118 degrees

Number of cutting edges Z: 2

Flute length  $L_c$ : 31 mm

Overall length L: 70 mm

Shank Ø  $D_s$ : 6.3 mm

Feed f in stainless steel < 900 N/mm<sup>2</sup>: 0.05 mm/rev.

**Technical description**

Overall length L	70 mm
Flute length $L_c$	31 mm
Tolerance nominal Ø	h8
Feed f in stainless steel < 900 N/mm <sup>2</sup>	0.05 mm/rev.
Nominal Ø $D_c$	6.3 mm

Shank $\varnothing D_s$	6.3 mm
Point angle	118 degrees
Standard	DIN 1897
Number of cutting edges Z	2
Coating	TiAlN
Tool material	HSS E
Shank	Plain shank
Through-coolant	no
Colour ring	green
Type of product	Jobber drill