

Garant
Stub drill HSS-E, TiAlN, Ø DC h8: 6,9 mm

Order data

Order number	113265 6,9
GTIN	4062406235000
Item class	11B

Description
Version:

High concentricity and **special chip flutes** ensure precise bores.

With point geometry shape C from size 2.4 mm.

Advantage:

Ideal for drilling shallow holes (approx. 2 - 4×D) on NC machines and automatic machines.

Recommendation:
Maximum drilling depth:

$$L_2 = L_C - 1.5 \times D_C$$

Through-coolant: no

Standard: DIN 1897

Tolerance nominal Ø: h8

Point angle: 118 degrees

Number of cutting edges Z: 2

Flute length L_C : 34 mm

Overall length L: 74 mm

Shank Ø D_s : 6.9 mm

Feed f in stainless steel < 900 N/mm²: 0.05 mm/rev.

Technical description

Tolerance nominal Ø	h8
Shank Ø D_s	6.9 mm
Point angle	118 degrees
Standard	DIN 1897
Nominal Ø D_C	6.9 mm

Flute length L_c	34 mm
Number of cutting edges Z	2
Overall length L	74 mm
Feed f in stainless steel < 900 N/mm ²	0.05 mm/rev.
Coating	TiAlN
Tool material	HSS E
Shank	Plain shank
Through-coolant	no
Colour ring	green
Type of product	Jobber drill