

Garant
Stub drill HSS-E-PM HPC, TiAlN, Ø DC h8: 5,1 mm

Order data

Order number	113280 5,1
GTIN	4062406232252
Item class	11B

Description
Version:

Tool made of sintered **powder metallurgy HSS** for heavy duty applications. Ground flutes with high concentricity. Generous flute profile.

With point geometry shape A/C from size 2.2 mm.

Advantage:

Can be used at increased cutting data.

Recommendation:
Maximum drilling depth:

flute length (see table) less 1.5×nominal Ø.

Machining strategy: HPC

Standard: DIN 1897

Tolerance nominal Ø: h8

Point angle: 130 degrees

Number of cutting edges Z: 2

Flute length L_c : 26 mm

Overall length L: 62 mm

Shank Ø D_s : 5.1 mm

Feed f in stainless steel < 900 N/mm²: 0.04 mm/rev.

Technical description

Number of cutting edges Z	2
Point angle	130 degrees
Shank Ø D_s	5.1 mm
Overall length L	62 mm

Standard	DIN 1897
Flute length L_c	26 mm
Feed f in stainless steel $< 900 \text{ N/mm}^2$	0.04 mm/rev.
Nominal $\varnothing D_c$	5.1 mm
Tolerance nominal \varnothing	h8
Coating	TiAlN
Tool material	HSS E PM
Shank	Plain shank
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	Jobber drill