



## Sheet metal drill HSS single-sided, uncoated, Ø DC h8: 4 mm



### Order data

Order number	113341 4
GTIN	4045197964281
Item class	12B

### Description

#### Version:

**Extremely break-resistant** due to short helix and strong core taper. Self-centring point.

**Cylindrically ground on circumference**(without chamfers) to prevent jamming.

Vaporised surface.

Dimensions similar to DIN 1897.

Point geometry shape C.

#### Application:

**Especially for drilling sheet metal.**

Through-coolant: no

Standard: DIN 1897

Tolerance nominal Ø: h8

Point angle: 135 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth L<sub>2</sub>: 8 mm

Flute length L<sub>c</sub>: 14 mm

Overall length L: 55 mm

### Technical description

Flute length L <sub>c</sub>	14 mm
Nominal Ø D <sub>c</sub>	4 mm
Tolerance nominal Ø	h8
Number of cutting edges Z	2
Standard	DIN 1897
recommended maximum drilling depth L <sub>2</sub>	8 mm

Overall length L	55 mm
Point angle	135 degrees
Coating	uncoated
Tool material	HSS
Through-coolant	no
Colour ring	without
Type of product	Jobber drill