

Garant

Jobber drill with 3 clamping faces HSS-E, uncoated, Ø DC h8: 1,6 mm



Order data

Order number	114001 1,6
GTIN	4045197764898
Item class	11B

Description

Version:

Particularly sturdy and robust due to the **strengthened core diameter**. Ground flutes, with high concentricity. Precision ground point. Three **drive flats on the shank** for use in a 3-jaw chuck.

Recommendation:

Maximum drilling depth:

$$L_2 = L_c - 1.5 \times D_c$$

Note:

Drills with plain shank, **without drive flats**

Through-coolant: no

Standard: DIN 338

Tolerance nominal Ø: h8

Point angle: 130 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth L_2 : 17.6 mm

Flute length L_c : 20 mm

Overall length L: 43 mm

Shank Ø D_s : 1.6 mm

Feed f in steel < 900 N/mm²: 0.03 mm/rev.

Technical description

Tolerance nominal Ø	h8
Feed f in steel < 900 N/mm ²	0.03 mm/rev.
Shank Ø D_s	1.6 mm
Overall length L	43 mm

Flute length L_c	20 mm
Standard	DIN 338
Number of cutting edges Z	2
Nominal $\varnothing D_c$	1.6 mm
recommended maximum drilling depth L_2	17.6 mm
Point angle	130 degrees
Coating	uncoated
Tool material	HSS E
Type	N
Shank	Three drive flats shank
Through-coolant	no
Colour ring	without
Type of product	Jobber drill