


HOLEX CleverDrill HSS jobber drill N, uncoated, Ø DC h8: 2,05 mm or inch

Order data

Order number	114030 2,05
GTIN	4045197850386
Item class	12B

Description
Version:

HOLEX CleverDrill: Sturdy drills for all standard applications. Improved spot drilling behaviour due to cross-ground form. Standard core thickness and core taper. Profile ground. Surface: Bronze-coloured tempered helical flutes.

Note:

Successor product for No. 114050 and No. 114160.

Size 13.2 – 20: With stepped shank Ø 12.7 mm.

Through-coolant: no

Standard: DIN 338

Tolerance nominal Ø: h8

Point angle: 130 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth L₂: 20.9 mm

Flute length L_c: 24 mm

Overall length L: 49 mm

Shank Ø D_s: 2.05 mm

Feed f in steel < 750 N/mm²: 0.03 mm/rev.

Technical description

Number of cutting edges Z	2
Overall length L	49 mm
Tolerance nominal Ø	h8
Nominal Ø D _c	2.05 mm
recommended maximum drilling depth L ₂	20.9 mm

Shank Ø D _s	2.05 mm
Standard	DIN 338
Flute length L _c	24 mm
Feed f in steel < 750 N/mm ²	0.03 mm/rev.
Point angle	130 degrees
Series	HOLEX CleverDrill
Coating	uncoated
Tool material	HSS
Type	N
Shank	Plain shank
Through-coolant	no
Colour ring	without
Type of product	Jobber drill