

Garant
HSS-E jobber drill, TiAlN, Ø DC h8: 7,6 mm

Order data

Order number	114580 7,6
GTIN	4045197855589
Item class	11B

Description
Version:

High performance drills for outstanding performance. Precision holes due to optimised diamond point geometry and 4-face grinding. The special flute profile yields a significant reduction in cutting forces.

Recommendation:
Maximum drilling depth:

$$L_2 = L_c - 1.5 \times D_c$$

Standard: DIN 338

Tolerance nominal Ø: h8

Point angle: 130 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth L_2 : 63.6 mm

Flute length L_c : 75 mm

Overall length L: 117 mm

Shank Ø D_s : 7.6 mm

Feed f in stainless steel > 900 N/mm²: 0.05 mm/rev.

Technical description

Shank Ø D_s	7.6 mm
Standard	DIN 338
Number of cutting edges Z	2
Nominal Ø D_c	7.6 mm
Flute length L_c	75 mm
Overall length L	117 mm

Feed f in stainless steel > 900 N/mm ²	0.05 mm/rev.
recommended maximum drilling depth L ₂	63.6 mm
Tolerance nominal Ø	h8
Point angle	130 degrees
Coating	TiAlN
Tool material	HSS E
Helix angle	35 degrees
Shank	Plain shank
Through-coolant	no
Colour ring	green
Type of product	Jobber drill