

**Garant**
**Jobber drill HSS-E-PM HPC, TiAlN, Ø DC h8: 5,7 mm**

**Order data**

Order number	114610 5,7
GTIN	4045197856418
Item class	11B

**Description**
**Version:**

With form S point.

**High-performance HPC twist drills** for high-alloy and high tensile materials. Particularly strong due to **strengthened core and a parabolic flute profile**. Point geometry with rake angle correction. Precise concentricity for exact holes.

**Recommendation:**
**Maximum drilling depth:**

$$L_2 = L_c - 1.5 \times D_c$$

Machining strategy: HPC

Standard: DIN 338

Tolerance nominal Ø: h8

Point angle: 130 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth  $L_2$ : 48.5 mm

Flute length  $L_c$ : 57 mm

Overall length L: 93 mm

Shank Ø  $D_s$ : 5.7 mm

Feed f in steel < 900 N/mm<sup>2</sup>: 0.05 mm/rev.

**Technical description**

Number of cutting edges Z	2
Overall length L	93 mm
Flute length $L_c$	57 mm
Nominal Ø $D_c$	5.7 mm
Tolerance nominal Ø	h8

recommended maximum drilling depth $L_2$	48.5 mm
Feed $f$ in steel $< 900 \text{ N/mm}^2$	0.05 mm/rev.
Standard	DIN 338
Shank $\varnothing D_s$	5.7 mm
Point angle	130 degrees
Coating	TiAlN
Tool material	HSS E PM
Helix angle	38 degrees
Shank	Plain shank
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	Jobber drill