

**Garant**
**Jobber drill HSS-E-PM HPC, TiAlN, Ø DC h8: 7,9 mm**

**Order data**

Order number	114610 7,9
GTIN	4045197856630
Item class	11B

**Description**
**Version:**

With form S point.

**High-performance HPC twist drills** for high-alloy and high tensile materials. Particularly strong due to **strengthened core and a parabolic flute profile**. Point geometry with rake angle correction. Precise concentricity for exact holes.

**Recommendation:**
**Maximum drilling depth:**

$$L_2 = L_c - 1.5 \times D_c$$

Machining strategy: HPC

Standard: DIN 338

Tolerance nominal Ø: h8

Point angle: 130 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth  $L_2$ : 63.2 mm

Flute length  $L_c$ : 75 mm

Overall length L: 117 mm

Shank Ø  $D_s$ : 7.9 mm

Feed f in steel < 900 N/mm<sup>2</sup>: 0.08 mm/rev.

**Technical description**

Flute length $L_c$	75 mm
Nominal Ø $D_c$	7.9 mm
recommended maximum drilling depth $L_2$	63.2 mm
Number of cutting edges Z	2
Overall length L	117 mm

Feed f in steel < 900 N/mm <sup>2</sup>	0.08 mm/rev.
Shank Ø D <sub>s</sub>	7.9 mm
Standard	DIN 338
Tolerance nominal Ø	h8
Point angle	130 degrees
Coating	TiAlN
Tool material	HSS E PM
Helix angle	38 degrees
Shank	Plain shank
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	Jobber drill