



HOLEX CleverDrill HSS jobber drill set No. 114030 in a case, uncoated, Type: 1-10,5



Order data

Order number	115050 1-10,5
GTIN	4045197875419
Item class	12B

Description

Version:

Composed of jobber drills DIN 338.

HOLEX CleverDrill: Sturdy drills for all standard applications. Improved spot drilling behaviour due to cross-ground form. Standard core thickness and core taper. Profile ground. Surface: Bronze-coloured tempered helical flutes.

Note:

Size 13.2 – 20: With stepped shank \varnothing 12.7 mm.

Through-coolant: no

Shank: Plain shank

Drill range: 1 - 10.5 mm

Number of drills: 24

Tapping hole \varnothing : 3.3; 4.2; 6.8; 10.2 mm

Incremental steps of drills: 0.5 mm

Technical description

Number of drills	24
------------------	----

Shank	Plain shank
Drill range	1 - 10.5 mm
Incremental steps of drills	0.5 mm
Tapping hole Ø	3.3; 4.2; 6.8; 10.2 mm
No. of teeth Z	2
Series	HOLEX CleverDrill
Coating	uncoated
Tool material	HSS
Standard	DIN 338
Type	N
Tolerance nominal Ø	h8
Point angle	130 degrees
Through-coolant	no
with case	yes
Colour ring	without
Type of product	Jobber drill