

Garant**Jobber drill long HSS N, uncoated, Ø DC h8: 12 mm****Order data**

Order number	116000 12
GTIN	4045197025685
Item class	11B

Description**Version:**

Vaporised from 2.4 mm. Particularly for deep hole drilling (for deep holes, repeated chip evacuation is necessary).

With point geometry shape A from size 4 mm.

Advantage:

Especially suitable for **long reach purposes**. (When used to drill deep holes, low feed rates and frequent drill pecks are necessary).

Recommendation:**Maximum drilling depth:**

$$L_2 = L_C - 1.5 \times D_C$$

Note:

Suitable NC spotting drills No. 112103, 112110 and 112160 with **120° tip angle** for enhanced process reliability.

Through-coolant: no

Standard: DIN 340

Tolerance nominal Ø: h8

Point angle: 118 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth L_2 : 116 mm

Flute length L_C : 134 mm

Overall length L: 205 mm

Shank Ø D_s : 12 mm

Feed f in steel < 750 N/mm²: 0.011 mm/rev.

Technical description

Nominal Ø D_C	12 mm
-----------------	-------

Feed f in steel < 750 N/mm ²	0.011 mm/rev.
Flute length L _c	134 mm
Number of cutting edges Z	2
Tolerance nominal Ø	h8
Shank Ø D _s	12 mm
Overall length L	205 mm
Standard	DIN 340
recommended maximum drilling depth L ₂	116 mm
Point angle	118 degrees
Coating	uncoated
Tool material	HSS
Type	N
Shank	Plain shank
Through-coolant	no
Colour ring	without
Type of product	Jobber drill