

Garant**Jobber drill extra long HSS N, uncoated, Ø DC h8 × overall length L: 2,5X140 mm****Order data**

Order number	116245 2,5X140
GTIN	4045197955517
Item class	11B

Description**Version:**

With precision ground point.

Vaporised high performance drills for drilling particularly deep holes. Take particular care to ensure **frequent chip clearance**.

Recommendation:

Maximum drilling depth:

Flute length L_c (see table) less $1.5 \times \varnothing D_c$.

Note:

Suitable NC spotting drills No. 112103, 112110 and 112160 with **120° tip angle** for enhanced process reliability

Through-coolant: no

Standard: DIN 1869

Tolerance nominal $\varnothing$: h8

Point angle: 118 degrees

Number of cutting edges Z: 2

Flute length L_c : 95 mm

Overall length L: 140 mm

Shank $\varnothing D_s$: 2.5 mm

Feed f in steel < 750 N/mm^2 : 0.05 mm/rev.

Technical description

Shank $\varnothing D_s$	2.5 mm
Flute length L_c	95 mm
Overall length L	140 mm

Number of cutting edges Z	2
Nominal Ø D _c	2.5 mm
Standard	DIN 1869
Feed f in steel < 750 N/mm ²	0.05 mm/rev.
Tolerance nominal Ø	h8
Point angle	118 degrees
Coating	uncoated
Tool material	HSS
Type	N
Helix angle	38 degrees
Shank	Plain shank
Through-coolant	no
Colour ring	without
Type of product	Jobber drill