

Garant

Jobber drill extra long HSS N, uncoated, Ø DC h8 × overall length L: 5,8X205 mm



Order data

Order number	116245 5,8X205
GTIN	4062406264727
Item class	11B

Description

Version:

With precision ground point.

Vaporised high performance drills for drilling particularly deep holes. Take particular care to ensure **frequent chip clearance**.

Recommendation:

Maximum drilling depth:

Flute length L_c (see table) less $1.5 \times \varnothing D_c$.

Note:

Suitable NC spotting drills No. 112103, 112110 and 112160 with **120° tip angle** for enhanced process reliability

Through-coolant: no

Standard: DIN 1869

Tolerance nominal \varnothing : h8

Point angle: 118 degrees

Number of cutting edges Z: 2

Flute length L_c : 140 mm

Overall length L: 205 mm

Shank $\varnothing D_s$: 5.8 mm

Feed f in steel < 750 N/mm²: 0.07 mm/rev.

Technical description

Feed f in steel < 750 N/mm ²	0.07 mm/rev.
Point angle	118 degrees
Shank $\varnothing D_s$	5.8 mm

Flute length L_c	140 mm
Standard	DIN 1869
Number of cutting edges Z	2
Tolerance nominal \varnothing	h8
Overall length L	205 mm
Nominal $\varnothing D_c$	5.8 mm
Coating	uncoated
Tool material	HSS
Type	N
Helix angle	38 degrees
Shank	Plain shank
Through-coolant	no
Colour ring	without
Type of product	Jobber drill