

## Garant

### Jobber drill extra long HSS N, uncoated, Ø DC h8 × overall length L: 7,5X370 mm



#### Order data

Order number	116245 7,5X370
GTIN	4062406264765
Item class	11B

#### Description

##### Version:

With precision ground point.

Vaporised high performance drills for drilling particularly deep holes. Take particular care to ensure **frequent chip clearance**.

##### Recommendation:

Maximum drilling depth:

Flute length  $L_c$  (see table) less  $1.5 \times \varnothing D_c$ .

##### Note:

Suitable NC spotting drills No. 112103, 112110 and 112160 with **120° tip angle** for enhanced process reliability

Through-coolant: no

Standard: DIN 1869

Tolerance nominal  $\varnothing$ : h8

Point angle: 118 degrees

Number of cutting edges Z: 2

Flute length  $L_c$ : 250 mm

Overall length L: 370 mm

Shank  $\varnothing D_s$ : 7.5 mm

Feed f in steel <  $750 \text{ N/mm}^2$ : 0.07 mm/rev.

#### Technical description

Standard	DIN 1869
Tolerance nominal $\varnothing$	h8
Nominal $\varnothing D_c$	7.5 mm

Feed f in steel < 750 N/mm <sup>2</sup>	0.07 mm/rev.
Overall length L	370 mm
Flute length L <sub>c</sub>	250 mm
Number of cutting edges Z	2
Point angle	118 degrees
Shank Ø D <sub>s</sub>	7.5 mm
Coating	uncoated
Tool material	HSS
Type	N
Helix angle	38 degrees
Shank	Plain shank
Through-coolant	no
Colour ring	without
Type of product	Jobber drill