

Garant

Jobber drill extra long HSS N, uncoated, Ø DC h8 × overall length L: 7X370 mm



Order data

Order number	116245 7X370
GTIN	4062406264758
Item class	11B

Description

Version:

With precision ground point.

Vaporised high performance drills for drilling particularly deep holes. Take particular care to ensure **frequent chip clearance**.

Recommendation:

Maximum drilling depth:

Flute length L_c (see table) less $1.5 \times \varnothing D_c$.

Note:

Suitable NC spotting drills No. 112103, 112110 and 112160 with **120° tip angle** for enhanced process reliability

Through-coolant: no

Standard: DIN 1869

Tolerance nominal \varnothing : h8

Point angle: 118 degrees

Number of cutting edges Z: 2

Flute length L_c : 250 mm

Overall length L: 370 mm

Shank $\varnothing D_s$: 7 mm

Feed f in steel < 750 N/mm^2 : 0.07 mm/rev.

Technical description

Point angle	118 degrees
Nominal $\varnothing D_c$	7 mm
Flute length L_c	250 mm

Shank $\varnothing D_s$	7 mm
Overall length L	370 mm
Tolerance nominal \varnothing	h8
Standard	DIN 1869
Number of cutting edges Z	2
Feed f in steel < 750 N/mm ²	0.07 mm/rev.
Coating	uncoated
Tool material	HSS
Type	N
Helix angle	38 degrees
Shank	Plain shank
Through-coolant	no
Colour ring	without
Type of product	Jobber drill