


HSS jobber drill N, uncoated, Ø DC h8: 43 mm

Order data

Order number	116320 43
GTIN	4045197955609
Item class	12C

Description
Version:

Special surface treatment, resulting in reduced tendency to edge build-up **and improved chip evacuation.**

Recommendation:
Maximum drilling depth:

$$L_2 = L_C - 1.5 \times D_C.$$

Note:

For suitable reducing adapters for tools with MT shanks see **No. 343000-343530.**

Through-coolant: no

Standard: DIN 345

Tolerance nominal Ø: h8

Point angle: 118 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth L_2 : 145.5 mm

Flute length L_C : 210 mm

Overall length L: 359 mm

Morse taper MT size: 4

Feed f in steel < 750 N/mm²: 0.32 mm/rev.

Technical description

Morse taper MT size	4
Tolerance nominal Ø	h8
Nominal Ø D_C	43 mm
Feed f in steel < 750 N/mm ²	0.32 mm/rev.

Number of cutting edges Z	2
Standard	DIN 345
Overall length L	359 mm
recommended maximum drilling depth L ₂	145.5 mm
Flute length L _c	210 mm
Point angle	118 degrees
Coating	uncoated
Tool material	HSS
Type	N
Helix angle	20-30 degrees
Shank	Morse taper
Through-coolant	no
Colour ring	without
Type of product	Jobber drill