

Garant
HSS core drill N, uncoated, Ø DC h8: 10,75 mm

Order data

Order number	116620 10,75
GTIN	4045197033604
Item class	11C

Description
Version:

Strong core. Sturdy jobber drill for better guidance in the hole

Advantage:

Particularly suitable **for drilling out** holes that are out of round. Misaligned holes can be aligned.

Recommendation:
Maximum drilling depth:

$$L_2 = L_C - 1.5 \times D_C$$

Note:
Please note:

Do not drill the respective tapping hole Ø (see table) less than the stated size.

For suitable reducing adapters for tools with MT shanks see **No. 343000-343530**.

Through-coolant: no

Standard: DIN 343

Tolerance nominal Ø: h8

Point angle: 120 degrees

Number of cutting edges Z: 3

recommended maximum drilling depth L_2 : 77.9 mm

Flute length L_C : 94 mm

Overall length L: 175 mm

Min. pre-drilling -Ø D_{min} : 7.7 mm

Morse taper MT size: 1

Feed f in steel < 750 N/mm²: 0.13 mm/rev.

Technical description

Overall length L	175 mm
Tolerance nominal Ø	h8

Flute length L_c	94 mm
Nominal $\varnothing D_c$	10.75 mm
Feed f in steel $< 750 \text{ N/mm}^2$	0.13 mm/rev.
recommended maximum drilling depth L_2	77.9 mm
Number of cutting edges Z	3
Standard	DIN 343
Morse taper MT size	1
Min. pre-drilling $-\varnothing D_{\min}$	7.7 mm
Point angle	120 degrees
Coating	uncoated
Tool material	HSS
Type	N
Shank	Morse taper
Through-coolant	no
Colour ring	without
Type of product	Jobber drill