

Garant**HSS core drill N, uncoated, Ø DC h8: 15,75 mm****Order data**

Order number	116620 15,75
GTIN	4045197033703
Item class	11C

Description**Version:**

Strong core. Sturdy jobber drill for better guidance in the hole

Advantage:

Particularly suitable **for drilling out** holes that are out of round. Misaligned holes can be aligned.

Note:**Please note:**

Do not drill the respective tapping hole Ø (see table) less than the stated size.

For suitable reducing adapters for tools with MT shanks see **No. 343000-343530**.

Through-coolant: no

Standard: DIN 343

Tolerance nominal Ø: h8

Point angle: 120 degrees

Number of cutting edges Z: 3

recommended maximum drilling depth L_2 : 96.375 mm

Flute length L_c : 120 mm

Overall length L: 218 mm

Min. pre-drilling -Ø D_{min} : 11.2 mm

Morse taper MT size: 2

Feed f in steel < 750 N/mm²: 0.17 mm/rev.

Technical description

Flute length L_c	120 mm
Number of cutting edges Z	3
Overall length L	218 mm
Standard	DIN 343

Morse taper MT size	2
Tolerance nominal Ø	h8
Feed f in steel < 750 N/mm ²	0.17 mm/rev.
recommended maximum drilling depth L ₂	96.375 mm
Nominal Ø D _c	15.75 mm
Min. pre-drilling -Ø D _{min}	11.2 mm
Point angle	120 degrees
Coating	uncoated
Tool material	HSS
Type	N
Shank	Morse taper
Through-coolant	no
Colour ring	without
Type of product	Jobber drill