

Garant
HSS core drill N, uncoated, Ø DC h8: 22,7 mm

Order data

Order number	116620 22,7
GTIN	4045197033840
Item class	11C

Description
Version:

Strong core. Sturdy jobber drill for better guidance in the hole

Advantage:

Particularly suitable **for drilling out** holes that are out of round. Misaligned holes can be aligned.

Note:
Please note:

Do not drill the respective tapping hole Ø (see table) less than the stated size.

For suitable reducing adapters for tools with MT shanks see **No. 343000-343530**.

Through-coolant: no

Standard: DIN 343

Tolerance nominal Ø: h8

Point angle: 120 degrees

Number of cutting edges Z: 3

recommended maximum drilling depth L_2 : 120.95 mm

Flute length L_c : 155 mm

Overall length L: 253 mm

Min. pre-drilling -Ø D_{min} : 16 mm

Morse taper MT size: 2

Feed f in steel < 750 N/mm²: 0.23 mm/rev.

Technical description

Overall length L	253 mm
Number of cutting edges Z	3
Standard	DIN 343
Feed f in steel < 750 N/mm ²	0.23 mm/rev.

recommended maximum drilling depth L_2	120.95 mm
Nominal $\varnothing D_c$	22.7 mm
Flute length L_c	155 mm
Morse taper MT size	2
Tolerance nominal \varnothing	h8
Min. pre-drilling $-\varnothing D_{min}$	16 mm
Point angle	120 degrees
Coating	uncoated
Tool material	HSS
Type	N
Shank	Morse taper
Through-coolant	no
Colour ring	without
Type of product	Jobber drill