

## Garant

**Diabolo solid carbide HPC drill, plain shank DIN 6535 HA, TiAlN, Ø DC h7 (mm or inch): 1,3 mm or inch**



### Order data

Order number	122361 1,3
GTIN	4045197967572
Item class	11E

### Description

#### Version:

Cutting chisel edge with **high centring accuracy** due to strong core and special point geometry. **Convex major cutting edges** with **defined honed edge** ensure the drill has high stability and maximum load capacity.

**Special multi-nano layer coating** for drilling in hardened steels.

#### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 122362 / 122372**.

Form **HE**: order with **No. 122361 / 122371 + 129100HE**.

Standard: DIN 6537 K

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth  $L_2$ : 5.1 mm

Overall length L: 45 mm

Shank Ø  $D_s$ : 4 mm

Feed f in steel < 60 HRC: 0.03 mm/rev.

### Technical description

recommended maximum drilling depth $L_2$	5.1 mm
Overall length L	45 mm
Standard	DIN 6537 K
Feed f in steel < 60 HRC	0.03 mm/rev.

Tolerance nominal $\varnothing$	h7
Nominal $\varnothing D_c$	1.3 mm
Number of cutting edges Z	2
Flute length $L_c$	7 mm
Shank $\varnothing D_s$	4 mm
Series	Diabolo
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	4xD
Type	H
Point angle	140 degrees
Shank	DIN 6535 HA to h6
Through-coolant	no
Machining strategy	HPC
Semi-Standard	yes
Colour ring	red
Type of product	Jobber drill