

Garant

**Diabolo solid carbide HPC drill, plain shank DIN 6535 HA, TiAlN, Ø DC h7:
13/32 mm or inch**


Order data

Order number	122361 13/32
GTIN	4062406116668
Item class	11E

Description
Version:

Cutting chisel edge with **high centring accuracy** due to strong core and special point geometry.
Convex major cutting edges with **defined honed edge** ensure the drill has high stability and maximum load capacity.

Special multi-nano layer coating for drilling in hardened steels.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 122362 / 122372**.

Form **HE**: order with **No. 122361 / 122371 + 129100HE**.

Standard: DIN 6537 K

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Semi-Standard: yes

Tolerance nominal Ø: h7

recommended maximum drilling depth L_2 : 39.52 mm

Overall length L: 102 mm

Shank Ø D_s : 12 mm

Feed f in steel < 60 HRC: 0.11 mm/rev.

Technical description

Shank Ø D_s	12 mm
recommended maximum drilling depth L_2	39.52 mm
Overall length L	102 mm

Tolerance nominal Ø	h7
Number of cutting edges Z	2
Inch nominal Ø corresponds to	10.32 mm
Flute length L _c	55 mm
Feed f in steel < 60 HRC	0.11 mm/rev.
Standard	DIN 6537 K
Semi-Standard	yes
Series	Diabolo
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	4xD
Type	H
Point angle	140 degrees
Shank	DIN 6535 HA to h6
Through-coolant	no
Machining strategy	HPC
Colour ring	red
Type of product	Jobber drill

Services

Shank grinding Type HE	129100 HE
------------------------	-----------