

Garant

Diabolo solid carbide HPC drill, plain shank DIN 6535 HA, TiAlN, Ø DC h7: 15,5 mm or inch



Order data

Order number	122361 15,5
GTIN	4062406098803
Item class	11E

Description

Version:

Cutting chisel edge with **high centring accuracy** due to strong core and special point geometry. **Convex major cutting edges** with **defined honed edge** ensure the drill has high stability and maximum load capacity.

Special multi-nano layer coating for drilling in hardened steels.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 122362 / 122372**.

Form **HE**: order with **No. 122361 / 122371 + 129100HE**.

Standard: DIN 6537 K

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Semi-Standard: yes

Tolerance nominal Ø: h7

recommended maximum drilling depth L_2 : 41.8 mm

Overall length L: 115 mm

Shank Ø D_s : 16 mm

Feed f in steel < 60 HRC: 0.13 mm/rev.

Technical description

Shank Ø D_s	16 mm
Nominal Ø D_c	15.5 mm
Number of cutting edges Z	2

Tolerance nominal \varnothing	h7
recommended maximum drilling depth L_2	41.8 mm
Feed f in steel < 60 HRC	0.13 mm/rev.
Flute length L_c	65 mm
Overall length L	115 mm
Standard	DIN 6537 K
Semi-Standard	yes
Series	Diabolo
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	4xD
Type	H
Point angle	140 degrees
Shank	DIN 6535 HA to h6
Through-coolant	no
Machining strategy	HPC
Colour ring	red
Type of product	Jobber drill

Services

Shank grinding Type HE	129100 HE
------------------------	-----------