

Garant

Diabolo solid carbide HPC drill, plain shank DIN 6535 HA, TiAlN, Ø DC h7 (mm or inch): 3/8 mm or inch


Order data

Order number	122371 3/8
GTIN	4062406116927
Item class	11E

Description
Version:

Cutting chisel edge with **high centring accuracy** due to strong core and special point geometry. **Convex major cutting edges** with **defined honed edge** ensure the drill has high stability and maximum load capacity.

Special multi-nano layer coating for drilling in hardened steels.

Recommendation:
Maximum drilling depth:

flute length (see table) less 1.5×nominal Ø.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 122362 / 122372**.

Form **HE**: order with **No. 122361 / 122371 + 129100HE**.

Standard: DIN 6537 K

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth L_2 : 32.705 mm

Overall length L: 89 mm

Shank Ø D_s : 10 mm

Feed f in steel < 1100 N/mm²: 0.27 mm/rev.

Feed f in steel < 60 HRC: 0.12 mm/rev.

Technical description

Standard	DIN 6537 K
----------	------------

Overall length L	89 mm
recommended maximum drilling depth L ₂	32.705 mm
Number of cutting edges Z	2
Shank Ø D _s	10 mm
Flute length L _c	47 mm
Tolerance nominal Ø	h7
Inch nominal Ø corresponds to	9.53 mm
Feed f in steel < 60 HRC	0.12 mm/rev.
Feed f in steel < 1100 N/mm ²	0.27 mm/rev.
Series	Diabolo
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	4×D
Type	H
Point angle	140 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	red
Type of product	Jobber drill

Services

Shank grinding Type HE	129100 HE
------------------------	-----------