



## HOLEX Pro Steel solid carbide drill, plain shank DIN 6535 HA, TiAlN, Ø DC h7: 7/16 mm or inch



### Order data

Order number	122504 7/16
GTIN	4062406110895
Item class	12F

### Description

#### Version:

#### HOLEX Pro Steel:

**Straight major cutting edges** and a **special flute profile** ensure good chip evacuation. The robust cutter geometry ensures high-performance drilling with good process reliability. A wide range of applications in steel materials thanks to a combination of tough ultra-fine grain carbide and extremely wear-resistant coating.

Up to Ø 1.9 with 4 facets, from Ø 2 with relieved cone.

#### Recommendation:

#### Maximum drilling depth:

flute length (see table) less  $1.5 \times$  nominal Ø.

#### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Version HB and HE supplied at the same price as HA.

Form **HB**: state **No. 122507**.

Form **HE**: state **No. 122508**.

Machining strategy: HPC

Standard: DIN 6537 K

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth  $L_2$ : 38.4 mm

Overall length L: 102 mm

Shank Ø  $D_s$ : 12 mm

Feed f in steel < 900 N/mm<sup>2</sup>: 0.22 mm/rev.

### Technical description

Feed f in steel < 900 N/mm <sup>2</sup>	0.22 mm/rev.
Inch nominal Ø corresponds to	11.11 mm
recommended maximum drilling depth L <sub>2</sub>	38.4 mm
Standard	DIN 6537 K
Overall length L	102 mm
Tolerance nominal Ø	h7
Flute length L <sub>c</sub>	55 mm
Shank Ø D <sub>s</sub>	12 mm
Number of cutting edges Z	2
Series	HOLEX Pro Steel
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	4xD
Point angle	140 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Colour ring	green
Type of product	Jobber drill