

**Garant**
**Solid carbide drill plain shank DIN 6535 HA 180°, TiAlN, Ø DC m7: 11,2 mm**

**Order data**

Order number	122506 11,2
GTIN	4062406090104
Item class	11E

**Description**
**Version:**

Special point geometry for generating **180° flat-bottomed holes**. Low radial forces even when spot drilling on faces with up to 45° slope. Flute geometry for optimum chip evacuation. With 4 guide chamfers to stabilise the drill in the hole.

**Advantage:**

**The 180° point angle** permits drilling and counterboring in a single operation.

**Recommendation:**

When using the solid carbide 180° drill it is absolutely essential for process reliability:

- **when spot drilling on flat surfaces to drill a pilot hole 1xD using pilot drill No. 122736.**
- **when spot drilling on sloping surfaces up to 15° : reduce the feed rate f to 50 %, up to 30°: reduce the feed rate f to 40 % and up to 45°: reduce the feed rate f to 25 % of the stated value. After spot drilling, the normal feed rate value can be used.**

**Note:**

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 122506 + 129100HB** .

Form **HE**: order with **No. 122506 + 129100HE**.

180° solid carbide drills for machining aluminium available on request.

**Not** suitable for generating counterbores for socket-head screws to DIN974-1.

Standard: Manufacturer's standard

Tolerance nominal Ø: m7

Number of cutting edges Z: 2

Semi-Standard: yes

Tolerance nominal Ø: m7

recommended maximum drilling depth  $L_2$ : 36.2 mm

Overall length L: 100 mm

Shank Ø  $D_s$ : 12 mm

Feed f in steel < 900 N/mm<sup>2</sup>: 0.15 mm/rev.

## Technical description

Overall length L	100 mm
Shank tolerance	h6
Shank $\varnothing D_s$	12 mm
Flute length $L_c$	53 mm
Feed f in steel < 900 N/mm <sup>2</sup>	0.15 mm/rev.
Nominal $\varnothing D_c$	11.2 mm
recommended maximum drilling depth $L_2$	36.2 mm
Number of cutting edges Z	2
Tolerance nominal $\varnothing$	m7
Standard	Manufacturer's standard
Semi-Standard	yes
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	3xD
Point angle	180 degrees
Shank	DIN 6535 HA to h6
Use for drilling	limited convexity
Use for drilling	limited cross-drilling
Use for drilling	limited oblique spot drilling
Through-coolant	yes, with 25 bar
Pilot drill required	yes, pilot drill
Colour ring	green
Type of product	Jobber drill

## Services

Shank grinding Type HB	129100 HB
Shank grinding Type HE	129100 HE

