

Garant

Solid carbide drill plain shank multi-directional fibre orientation DIN 6535 HA, Diamond, Ø DC m7: 10,5 mm



Order data

Order number	122512 10,5
GTIN	4062406349073
Item class	11Y

Description

IMPORTANT: item is configurable

Nominal Ø D_C: 10.5 mm

Ø range (1/100 size): 10.01 - 10.99 mm, Intervall: 0,010

Version:

With the latest generation of **crystalline diamond coating sp³**, for process reliability in machining **fibre-reinforced composites, CRP, GRP, and graphite. With 90° point angle** and special geometry to **avoid delamination.**

With guide chamfer for materials with **multi-directional** fibre orientation.

Recommendation:

Maximum drilling depth:

Flute length (see table) less 1.5×nominal Ø.

Note:

Flute length $L_C = L_2 + 1.5 \times D_C$.

Available in **1/100 sizes** and according to the table.

Through-coolant: no

Tolerance nominal Ø: m7

Number of cutting edges Z: 2

Ø range (1/100 size): 10.01 - 10.99 mm

recommended maximum drilling depth L₂: 55.3 mm

Overall length L: 118 mm

Shank Ø D_s: 12 mm

Feed f in GRP CRP: 0.19 mm/rev.

Technical description

recommended maximum drilling depth L ₂	55.3 mm
---	---------

Nominal $\varnothing D_c$	10.5 mm
Number of cutting edges Z	2
\varnothing range (1/100 size)	10.01 - 10.99 mm
Shank tolerance	h6
Flute length L_c	71 mm
Shank $\varnothing D_s$	12 mm
Overall length L	118 mm
Tolerance nominal \varnothing	m7
Feed f in GRP CRP	0.19 mm/rev.
Coating	Diamond
Tool material	Solid carbide
Standard	Manufacturer's standard
Drill depth up to	5xD
Point angle	90 degrees
Shank	DIN 6535 HA to h6
Through-coolant	no
Colour ring	black
Type of product	Jobber drill