

## Garant

### Solid carbide HPC drill, plain shank DIN 6535 HA, DLC, Ø DC h7: 1,8 mm



#### Order data

|              |               |
|--------------|---------------|
| Order number | 122602 1,8    |
| GTIN         | 4045197752208 |
| Item class   | 11E           |

#### Description

##### Version:

**DLC coating sp<sup>2</sup>** of the latest generation with **low coefficient of friction** results in **outstanding chip clearance**. For **high-performance milling** of **aluminium materials**. **High alignment accuracy** and **roundness of the hole**, thanks to **6 guide chamfers**.

Size 1 - 1.5 with 4 guide chamfers.

##### Recommendation:

##### Maximum drilling depth:

flute length (see table) less 1.5×nominal Ø.

##### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 122603**.

Form **HE**: order with **No. 122602 + 129100HE**.

Standard: DIN 6537

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Semi-Standard: yes

Tolerance nominal Ø: h7

recommended maximum drilling depth  $L_2$ : 13.3 mm

Overall length L: 55 mm

Shank Ø  $D_s$ : 4 mm

Feed f in aluminium short-chipping: 0.2 mm/rev.

#### Technical description

|                    |       |
|--------------------|-------|
| Shank tolerance    | h6    |
| Flute length $L_c$ | 16 mm |

|  |                   |
|--|-------------------|
| Number of cutting edges Z                | 2                 |
| Feed f in aluminium short-chipping       | 0.2 mm/rev.       |
| Standard                                 | DIN 6537          |
| Tolerance nominal $\varnothing$          | h7                |
| Overall length L                         | 55 mm             |
| Shank $\varnothing D_s$                  | 4 mm              |
| Nominal $\varnothing D_c$                | 1.8 mm            |
| recommended maximum drilling depth $L_2$ | 13.3 mm           |
| Semi-Standard                            | yes               |
| Coating                                  | DLC               |
| Tool material                            | solid carbide     |
| Drill depth up to                        | 6×D               |
| Type                                     | W                 |
| Point angle                              | 135 degrees       |
| Shank                                    | DIN 6535 HA to h6 |
| Through-coolant                          | yes, with 25 bar  |
| Machining strategy                       | HPC               |
| Colour ring                              | yellow            |
| Type of product                          | Jobber drill      |