

Garant
Solid carbide HPC drill, plain shank DIN 6535 HA, DLC, Ø DC h7: 1,9 mm

Order data

Order number	122602 1,9
GTIN	4045197752222
Item class	11E

Description
Version:

DLC coating sp² of the latest generation with **low coefficient of friction** results in **outstanding chip clearance**. For **high-performance milling** of **aluminium materials**. **High alignment accuracy** and **roundness of the hole**, thanks to **6 guide chamfers**.

Size 1 - 1.5 with 4 guide chamfers.

Recommendation:
Maximum drilling depth:

flute length (see table) less 1.5×nominal Ø.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 122603**.

Form **HE**: order with **No. 122602 + 129100HE**.

Standard: DIN 6537

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Semi-Standard: yes

Tolerance nominal Ø: h7

recommended maximum drilling depth L_2 : 13.2 mm

Overall length L: 55 mm

Shank Ø D_s : 4 mm

Feed f in aluminium short-chipping: 0.2 mm/rev.

Technical description

Overall length L	55 mm
Feed f in aluminium short-chipping	0.2 mm/rev.

Flute length L_c	16 mm
Number of cutting edges Z	2
Shank $\varnothing D_s$	4 mm
Standard	DIN 6537
Shank tolerance	h6
Nominal $\varnothing D_c$	1.9 mm
Tolerance nominal \varnothing	h7
recommended maximum drilling depth L_2	13.2 mm
Semi-Standard	yes
Coating	DLC
Tool material	solid carbide
Drill depth up to	6×D
Type	W
Point angle	135 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Colour ring	yellow
Type of product	Jobber drill