

Garant

Solid carbide HPC drill plain shank DIN 6535 HA, TiAlN, Ø DC h7: 15,5 mm



Order data

| | |
|--------------|---------------|
| Order number | 122690 15,5 |
| GTIN | 4062406093068 |
| Item class | 11E |

Description

Version:

3 guide chamfers for particularly high accuracy and surface quality at tight hole tolerances.
Asymmetrical tip geometry for **very high metal removal rates**. New generation of **innovative high-performance drills for cast iron** in the HPC field.

Advantage:

For HPC high performance drilling in castings. **Outstandingly suitable for bainite cast iron (ADI)**.

Recommendation:

Maximum drilling depth:

Flute length (see table) less 1.5×nominal Ø.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 122690 + 129100HB**.

Form **HE**: order with **No. 122690 + 129100HE**.

Standard: DIN 6537

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth L_2 : 59.8 mm

Overall length L: 133 mm

Shank Ø D_s : 16 mm

Feed f in GJS ADI > 800 N/mm²: 0.39 mm/rev.

Technical description

| | |
|---|--------------|
| Feed f in GJS ADI > 800 N/mm ² | 0.39 mm/rev. |
|---|--------------|

| | |
|--|-------------------|
| Tolerance nominal \varnothing | h7 |
| Shank $\varnothing D_s$ | 16 mm |
| Standard | DIN 6537 |
| Flute length L_c | 83 mm |
| recommended maximum drilling depth L_2 | 59.8 mm |
| Number of cutting edges Z | 2 |
| Overall length L | 133 mm |
| Nominal $\varnothing D_c$ | 15.5 mm |
| Coating | TiAlN |
| Tool material | Solid carbide |
| Drill depth up to | 6xD |
| Point angle | 135 degrees |
| Shank | DIN 6535 HA to h6 |
| Through-coolant | yes, with 25 bar |
| Machining strategy | HPC |
| Semi-Standard | yes |
| Colour ring | white |
| Type of product | Jobber drill |

Services

| | |
|------------------------|-----------|
| Shank grinding Type HE | 129100 HE |
| Shank grinding Type HB | 129100 HB |