

Garant

Solid carbide HPC drill plain shank DIN 6535 HA, TiAlN, Ø DC h7: 16,8 mm



Order data

Order number	122690 16,8
GTIN	4062406093099
Item class	11E

Description

Version:

3 guide chamfers for particularly high accuracy and surface quality at tight hole tolerances.
Asymmetrical tip geometry for **very high metal removal rates**. New generation of **innovative high-performance drills for cast iron** in the HPC field.

Advantage:

For HPC high performance drilling in castings. **Outstandingly suitable for bainite cast iron (ADI)**.

Recommendation:

Maximum drilling depth:

Flute length (see table) less 1.5×nominal Ø.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 122690 + 129100HB**.

Form **HE**: order with **No. 122690 + 129100HE**.

Standard: DIN 6537

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth L_2 : 67.8 mm

Overall length L: 143 mm

Shank Ø D_s : 18 mm

Feed f in GJS ADI > 800 N/mm²: 0.43 mm/rev.

Technical description

Feed f in GJS ADI > 800 N/mm ²	0.43 mm/rev.
---	--------------

Shank $\varnothing D_s$	18 mm
Nominal $\varnothing D_c$	16.8 mm
Flute length L_c	93 mm
recommended maximum drilling depth L_2	67.8 mm
Tolerance nominal \varnothing	h7
Number of cutting edges Z	2
Overall length L	143 mm
Standard	DIN 6537
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	6xD
Point angle	135 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	white
Type of product	Jobber drill

Services

Shank grinding Type HE	129100 HE
Shank grinding Type HB	129100 HB