

Garant

GARANT Master Steel SPEED solid carbide drill, plain shank DIN 6535 HA, TiAlN, Ø DC h7: 18,9 mm


Order data

Order number	122715 18,9
GTIN	4062406401146
Item class	11E

Description
Version:

Developed for use with **very high cutting speeds**. Outstandingly suitable for machines with **low power output** and high speeds.

- **Clear reduction in cutting forces due to special cutter geometry.**
- **Coating for best wear resistance even at high process temperatures.**
- **Polished flutes for good chip clearance.**

A **slim chisel edge** and the **special arrangement of the 4 guide chamfers** ensure **high positioning and alignment accuracy**. Optimised micro-geometry for increased working life and performance capability.

Recommendation:
Maximum drilling depth:

flute length (see table) less 1.5×nominal Ø.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 122716**.

Form **HE**: order with **No. 122715 + 129100HE**.

Standard: DIN 6537

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth L_2 : 72.7 mm

Overall length L: 153 mm

Shank Ø D_s : 20 mm

Feed f in steel < 1100 N/mm²: 0.38 mm/rev.

Technical description

recommended maximum drilling depth L_2	72.7 mm
Flute length L_c	101 mm
Shank $\varnothing D_s$	20 mm
Number of cutting edges Z	2
Overall length L	153 mm
Feed f in steel < 1100 N/mm ²	0.38 mm/rev.
Standard	DIN 6537
Tolerance nominal $\varnothing$	h7
Nominal $\varnothing D_c$	18.9 mm
Series	GARANT Master Steel
Coating	TiAlN
Tool material	solid carbide
Drill depth up to	6xD
Point angle	135 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	green
Type of product	Jobber drill