

**HOLEX**
**Solid carbide drill plain shank DIN 6535 HB, TiAlN, Ø DC m7 (mm or inch): 18,5 mm or inch**

**Order data**

Order number	122772 18,5
GTIN	4062406150006
Item class	12F

**Description**
**Version:**

Tool specially matched to drilling holes without through-coolant. **Concave major cutting edges** and a **special flute profile** ensure a good chip evacuation. The sturdy cutter geometry with **special point geometry** and 4 cutting edges ensures drilling with good process reliability. A wide range of applications in steel materials thanks to a combination of tough ultra-fine grain carbide and extremely **wear-resistant** and **heat-resistant coating**.

**Recommendation:**
**Maximum drilling depth:**

Flute length (see table) less 1.5×nominal Ø.

**Note:**

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Through-coolant: no

Standard: DIN 6537

Tolerance nominal Ø: m7

Number of cutting edges Z: 2

Tolerance nominal Ø: m7

recommended maximum drilling depth  $L_2$ : 73.25 mm

Overall length L: 153 mm

Shank Ø  $D_s$ : 20 mm

Feed f in steel < 900 N/mm<sup>2</sup>: 0.28 mm/rev.

**Technical description**

Number of cutting edges Z	2
Tolerance nominal Ø	m7

recommended maximum drilling depth $L_2$	73.25 mm
Overall length L	153 mm
Shank $\varnothing D_s$	20 mm
Flute length $L_c$	101 mm
Nominal $\varnothing D_c$	18.5 mm
Feed f in steel < 900 N/mm <sup>2</sup>	0.28 mm/rev.
Standard	DIN 6537
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	6×D
Point angle	140 degrees
Shank	DIN 6535 HB to h6
Through-coolant	no
Colour ring	green
Type of product	Jobber drill