

HOLEX
Solid carbide drill plain shank DIN 6535 HE, TiAlN, Ø DC m7 (mm or inch): 18,5 mm or inch

Order data

Order number	122773 18,5
GTIN	4062406151447
Item class	12F

Description
Version:

Tool specially matched to drilling holes without through-coolant. **Concave major cutting edges** and a **special flute profile** ensure a good chip evacuation. The sturdy cutter geometry with **special point geometry** and 4 cutting edges ensures drilling with good process reliability. A wide range of applications in steel materials thanks to a combination of tough ultra-fine grain carbide and extremely **wear-resistant** and **heat-resistant coating**.

Recommendation:
Maximum drilling depth:

Flute length (see table) less 1.5×nominal Ø.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Standard: DIN 6537

Tolerance nominal Ø: m7

Number of cutting edges Z: 2

Tolerance nominal Ø: m7

recommended maximum drilling depth L_2 : 73.25 mm

Overall length L: 153 mm

Shank Ø D_s : 20 mm

Feed f in steel < 900 N/mm²: 0.28 mm/rev.

Technical description

Tolerance nominal Ø	m7
Overall length L	153 mm
Number of cutting edges Z	2

recommended maximum drilling depth L_2	73.25 mm
Standard	DIN 6537
Shank $\varnothing D_s$	20 mm
Feed f in steel $< 900 \text{ N/mm}^2$	0.28 mm/rev.
Nominal $\varnothing D_c$	18.5 mm
Flute length L_c	101 mm
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	6×D
Point angle	140 degrees
Shank	DIN 6535 HE to h6
Through-coolant	no
Colour ring	green
Type of product	Jobber drill