

Garant

Solid carbide drill-reamer with plain shank DIN 6535 HA, TiAlN, Ø DC: 12,68 mm



Order data

Order number	122795 12,68
GTIN	4062406102876
Item class	11P

Description

Version:

Drilling and reaming in a single operation. Very high concentricity. With **4 reaming cutting edges** for optimum dimensional accuracy and surface quality as good as reaming.

Recommendation:

Maximum drilling depth:

flute length (see table) less 1.5×nominal Ø.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 122795 + 129100HB**.

Form **HE**: order with **No. 122795 + 129100HE**.

Through-coolant: yes, with 25 bar

Bore Ø tolerance: ±0.003

Standard: Manufacturer's standard

Number of cutting edges Z: 2

Bore Ø tolerance: ±0.003

recommended maximum drilling depth L_2 : 58 mm

Overall length L: 124 mm

Shank Ø D_s : 14 mm

Feed f in steel < 900 N/mm²: 0.32 mm/rev.

Technical description

recommended maximum drilling depth L_2	58 mm
Overall length L	124 mm

Nominal $\varnothing D_c$	12.68 mm
Shank $\varnothing D_s$	14 mm
Standard	Manufacturer's standard
Feed f in steel < 900 N/mm ²	0.32 mm/rev.
Flute length L_c	77 mm
Shank tolerance	h6
Number of cutting edges Z	2
Bore \varnothing tolerance	± 0.003
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	5xD
Point angle	140 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Colour ring	without
Type of product	Jobber drill

Services

Shank grinding Type HB	129100 HB
Shank grinding Type HE	129100 HE