

## Garant

### Solid carbide drill-reamer with plain shank DIN 6535 HA, TiAlN, Ø DC: 9 mm



#### Order data

Order number	122795 9
GTIN	4062406102388
Item class	11P

#### Description

##### Version:

**Drilling and reaming in a single operation.** Very high concentricity. With **4 reaming cutting edges** for optimum dimensional accuracy and surface quality as good as reaming.

##### Recommendation:

##### Maximum drilling depth:

flute length (see table) less  $1.5 \times \text{nominal } \varnothing$ .

##### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 122795 + 129100HB**.

Form **HE**: order with **No. 122795 + 129100HE**.

Through-coolant: yes, with 25 bar

Bore  $\varnothing$  tolerance: H7

Standard: Manufacturer's standard

Number of cutting edges Z: 2

Bore  $\varnothing$  tolerance: H7

recommended maximum drilling depth  $L_2$ : 47.5 mm

Overall length L: 103 mm

Shank  $\varnothing D_s$ : 10 mm

Feed f in steel  $< 900 \text{ N/mm}^2$ : 0.23 mm/rev.

#### Technical description

recommended maximum drilling depth $L_2$	47.5 mm
Shank tolerance	h6
Number of cutting edges Z	2

Flute length $L_c$	61 mm
Shank $\varnothing D_s$	10 mm
Nominal $\varnothing D_c$	9 mm
Standard	Manufacturer's standard
Overall length L	103 mm
Feed f in steel < 900 N/mm <sup>2</sup>	0.23 mm/rev.
Bore $\varnothing$ tolerance	H7
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	5×D
Point angle	140 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Colour ring	without
Type of product	Jobber drill

## Services

Shank grinding Type HE	129100 HE
Shank grinding Type HB	129100 HB