Garant

Solid carbide HPC drill, plain shank DIN 6535 HA, DLC, ⌀ DC h7: 7,3 mm



Order data

Order number	122808 7,3
GTIN	4045197754073
Item class	11E

Description

Version:
DLC coating sp^2 of the latest generation with **low coefficient of friction** results in **outstanding chip clearance.** For **high-performance milling** of **aluminium materials**. **High roundness** and **alignment accuracy of the deep hole**, thanks to **6 guide chamfers.**
Recommendation:
Maximum drilling depth:
flute length (see table) less 1.5×nominal ⌀.
Note:
Flute length $L_C = L_2 + 1.5 \times D_C$.
Form HB and HE supplied at the same price as HA.
Form **HB:** order with **No. 122809**.
Form **HE:** order with **No. 122808 + 129100HE**.
Standard: Manufacturer's standard
Tolerance nominal ⌀: h7
Number of cutting edges Z: 2
Tolerance nominal ⌀: h7
recommended maximum drilling depth L_2: 65.1 mm
Overall length L: 114 mm
Shank ⌀ D_s: 8 mm
Feed f in aluminium short-chipping: 0.45 mm/rev.

Technical description

Shank ⌀ D_s	8 mm
Tolerance nominal ⌀	h7
Overall length L	114 mm

Flute length L_c	76 mm
Nominal ⌀ D_C	7.3 mm
Feed f in aluminium short-chipping	0.45 mm/rev.
Number of cutting edges Z	2
Standard	Manufacturer's standard
Shank tolerance	h6
recommended maximum drilling depth L_2	65.1 mm
Coating	DLC
Tool material	solid carbide
Drill depth up to	8×D
Type	W
Point angle	135 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	yellow
Type of product	Jobber drill

Services

Shank grinding Type HE	129100 HE