

Garant**Solid carbide HPC drill, plain shank DIN 6535 HA, DLC, Ø DC h7: 7,6 mm****Order data**

Order number	122808 7,6
GTIN	4045197754103
Item class	11E

Description**Version:**

DLC coating sp^2 of the latest generation with **low coefficient of friction** results in **outstanding chip clearance**. For **high-performance milling** of **aluminium materials**. **High roundness** and **alignment accuracy of the deep hole**, thanks to **6 guide chamfers**.

Recommendation:**Maximum drilling depth:**

flute length (see table) less $1.5 \times \text{nominal } \varnothing$.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 122809**.

Form **HE**: order with **No. 122808 + 129100HE**.

Standard: Manufacturer's standard

Tolerance nominal $\varnothing$: h7

Number of cutting edges Z: 2

Tolerance nominal $\varnothing$: h7

recommended maximum drilling depth L_2 : 64.6 mm

Overall length L: 114 mm

Shank $\varnothing D_s$: 8 mm

Feed f in aluminium short-chipping: 0.45 mm/rev.

Technical description

Shank tolerance	h6
Nominal $\varnothing D_c$	7.6 mm
Standard	Manufacturer's standard

Flute length L_c	76 mm
Shank $\varnothing D_s$	8 mm
Tolerance nominal $\varnothing$	h7
Number of cutting edges Z	2
Feed f in aluminium short-chipping	0.45 mm/rev.
Overall length L	114 mm
recommended maximum drilling depth L_2	64.6 mm
Coating	DLC
Tool material	solid carbide
Drill depth up to	8×D
Type	W
Point angle	135 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	yellow
Type of product	Jobber drill

Services

Shank grinding Type HE	129100 HE
------------------------	-----------