

Garant

Solid carbide HPC drill plain shank DIN 6535 HA, TiAlN, Ø DC m6 (mm or inch): 7/16 mm or inch



Order data

| | |
|--------------|---------------|
| Order number | 123008 7/16 |
| GTIN | 4062406116064 |
| Item class | 11E |

Description

Version:

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry**. High roundness and alignment accuracy of the deep hole, thanks to **4 guide chamfers**. Outstanding chip evacuation due to **4 internal cooling channels** from Ø 3.8 mm. Up to 3.7 mm Ø with 2 internal cooling channels. **Straight major cutting edges** with honed edges and special flute profile for **short chips**, even on long chipping materials.

Recommendation:

Maximum drilling depth:

Flute length (see table) less 1.5×nominal Ø.

Note:

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 123010**.

Form **HE**: order with **No. 123008 + 129100HE**.

Flute length $L_c = L_2 + 1.5 \times D_c$

Standard: Manufacturer's standard

Tolerance nominal Ø: m6

Number of cutting edges Z: 2

Semi-Standard: yes

Tolerance nominal Ø: m6

recommended maximum drilling depth L_2 : 97.2 mm

Overall length L: 162 mm

Shank Ø D_s : 12 mm

Feed f in stainless steel > 900 N/mm²: 0.15 mm/rev.

Technical description

| | |
|--|-------------------------|
| Shank tolerance | h6 |
| Shank $\varnothing D_s$ | 12 mm |
| Flute length L_c | 114 mm |
| Overall length L | 162 mm |
| Standard | Manufacturer's standard |
| Feed f in stainless steel $> 900 \text{ N/mm}^2$ | 0.15 mm/rev. |
| Number of cutting edges Z | 2 |
| Inch nominal \varnothing corresponds to | 11.11 mm |
| recommended maximum drilling depth L_2 | 97.2 mm |
| Tolerance nominal \varnothing | m6 |
| Semi-Standard | yes |
| Coating | TiAlN |
| Tool material | Solid carbide |
| Drill depth up to | 8xD |
| Point angle | 140 degrees |
| Shank | DIN 6535 HA to h6 |
| Through-coolant | yes, with 25 bar |
| Machining strategy | HPC |
| Colour ring | blue |
| Type of product | Jobber drill |

Services

| | |
|------------------------|-----------|
| Shank grinding Type HE | 129100 HE |
|------------------------|-----------|