



HOLEX Pro Steel solid carbide drill, plain shank DIN 6535 HA, TiAlN, Ø DC h7: 11,3 mm



Order data

Order number	123103 11,3
GTIN	4062406093310
Item class	12F

Description

Version:

HOLEX Pro Steel:

Straight major cutting edges and a **special flute profile** ensure good chip evacuation. The robust cutting edge geometry ensures high-performance drilling with good process reliability. A wide range of applications in steel materials thanks to a combination of tough ultra-fine grain carbide and extremely wear-resistant coating.

Recommendation:

Maximum drilling depth:

Flute length (see table) less 1.5×nominal Ø.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Version HB and HE supplied at the same price as HA.

Form **HB**: state **No. 123104**.

Form **HE**: state **No. 123109**.

Machining strategy: HPC

Standard: Manufacturer's standard

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth L_2 : 97.1 mm

Overall length L: 162 mm

Shank Ø D_s : 12 mm

Feed f in steel < 900 N/mm²: 0.2 mm/rev.

Technical description

Standard	Manufacturer's standard
Feed f in steel $< 900 \text{ N/mm}^2$	0.2 mm/rev.
Nominal $\varnothing D_c$	11.3 mm
Shank $\varnothing D_s$	12 mm
Number of cutting edges Z	2
Flute length L_c	114 mm
Tolerance nominal \varnothing	h7
Overall length L	162 mm
recommended maximum drilling depth L_2	97.1 mm
Series	HOLEX Pro Steel
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	8×D
Point angle	135 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Colour ring	green
Type of product	Jobber drill