

## Garant

### Solid carbide HPC drill, plain shank DIN 6535 HA, DLC, Ø DC h7: 12,8 mm



#### Order data

Order number	123178 12,8
GTIN	4045197755650
Item class	11E

#### Description

##### Version:

**DLC coating**  $sp^2$  of the latest generation with **low coefficient of friction** results in **outstanding chip clearance**. For **high-performance milling** of **aluminium materials**. **High roundness** and **alignment accuracy of the deep hole**, thanks to **6 guide chamfers**.

##### Recommendation:

##### Maximum drilling depth:

flute length (see table) less  $1.5 \times \text{nominal } \varnothing$ .

##### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

For process reliability when using the  $12 \times D$  drill, an initial centre drilling with NC spotting drills No. 121068– 121130 is necessary.

Form HB and HE are supplied at the same price as HA.

Order form **HB**: with **No. 123179**.

Order form **HE**: with **No. 123178 + 129100HE**.

Standard: Manufacturer's standard

Tolerance nominal  $\varnothing$ : h7

Number of cutting edges Z: 2

Semi-Standard: yes

Tolerance nominal  $\varnothing$ : h7

recommended maximum drilling depth  $L_2$ : 162.8 mm

Overall length L: 230 mm

Shank  $\varnothing D_s$ : 14 mm

Feed f in aluminium short-chipping: 0.65 mm/rev.

#### Technical description

Nominal $\varnothing D_c$	12.8 mm
---------------------------	---------

Shank tolerance	h6
Tolerance nominal $\varnothing$	h7
Flute length $L_c$	182 mm
Standard	Manufacturer's standard
Overall length L	230 mm
Feed f in aluminium short-chipping	0.65 mm/rev.
Number of cutting edges Z	2
Shank $\varnothing D_s$	14 mm
recommended maximum drilling depth $L_2$	162.8 mm
Semi-Standard	yes
Coating	DLC
Tool material	solid carbide
Drill depth up to	12xD
Type	W
Point angle	135 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Colour ring	yellow
Type of product	Jobber drill

## Services

Shank grinding Type HE	129100 HE
------------------------	-----------